

EUROPEAN MODEL

# TWISTER T4 SE



Customize Your Trim Speed

T4	Type	Feed (lbs/hr)	Feed (kg/hr)
1	Wet	Up to 23	Up to 11
2	Wet	Up to 51	Up to 23
3	Wet	Up to 81	Up to 37
4	Wet	Up to 113	Up to 51
1	Dry	Up to 7	Up to 3
2	Dry	Up to 16	Up to 7

WATCH IT IN ACTION

[TWISTERTRIMMER.COM/TWISTER-T4-TRIMMER](http://TWISTERTRIMMER.COM/TWISTER-T4-TRIMMER)



Triple System



Tandem System



## T4 SE Trimmer Features

- Lightweight
- Portable with its two-piece design
- Adjustable feet to allow incline
- 304 stainless steel tumbler
- Nitrided steel blades
- Stainless steel high air flow guard
- Scale up to 3 wet / 2 dry in a row
- Control box with digital controls
- Speed control of tumbler
- Speed control of blades
- Airflow control (Vacuum Bypass)



EUROPEAN MODEL

# TWISTER T4 SE



**ADDITIONAL  
REQUIREMENTS**

Extension Cord

12 AWG (Minimum AWG Size)

7.6m / 25ft max length

T4 LEAF TRIMMER

T4 LEAF COLLECTOR

**CONNECTOR  
(PLUG)**

CEE 7/7



CEE 7/7



**SPECIFICATIONS**

Product Number	24-9019-00-P
Input Voltage	230V, 60 Hz
Current Draw	2A
Blade Motor	200W
Blade Speed	980-1875 RPM
Tumbler Motor	6W
Tumbler Speed	47-96 RPM
Tumbler Diameter	5in / 10.1cm
Tumbler Slots	40 x .25in/.6cm
Cut Height	.040in / 1mm
Weight	56lbs / 25.4kg
Shipping Weight (w/ T4-LC)	120lbs / 54.4kg
Length	25in / 63.5cm
Width	15in / 38.1cm
Height	16.5in / 42cm
Circuit Breaker Required	10A / 230V
Connector (plug)	CEE 7/7
Filter Bag Included	70 Micron

**ACCESSORIES & COMPONENTS**

T4 Leaf Collector	23-0170E-01-P
T4 Trim Saver	23-10025A
T4 Stand (no vacuum)	23-0229-00
T4 Stainless Steel Stand (no vacuum)	23-0030
T4 Rail (Tandem)	24-0140-P
T4 Rail (Triple)	24-0139-P
Feed Conveyor (Inbound)	26-0001-02
Quality Conveyor (Outbound)	26-0002-02
Feed Conveyor (Extra Tall for T4 Rail)	26-0102-00

Visit [twistertrimmer.com](http://twistertrimmer.com) or call your Twister Rep for an extensive list of replacement parts or accessories.



**TWISTER**