

# TWISTER

## TRIM SAVER

Maximize Profit Without Wasting Your Trim



w/o Trim Saver



w/ Trim Saver



### Trim Saver Features

- FDA approved stainless steel bin
- FDA approved lid & fasteners
- FDA approved silicone bin lid seal
- FDA approved silicone cyclone gaskets



# TWISTER

## T 4 TRIM SAVER



TESTED

### ADDITIONAL REQUIREMENTS

Extension Cord

12 AWG (Minimum AWG Size)

7.6m / 25ft max length

### CONNECTOR (PLUG)

NEMA 5-15P



### CS-12 T4 TRIM SAVER SPECIFICATIONS

Product Number	23-0201-01-P
Input Voltage	120V, 60Hz
Motor	1.5HP, 1,125W Fan-Cooled
Amps (running)	12A
Amps (startup)	53A
Motor Speed	3450RPM
Airflow Capacity	1200 CFM
Static Pressure	10" W.G.
Operating Conditions	650ACFM @ 5" W.G.
Impeller	10in / 254mm
Hose Size	5in / 153mm
Height	62"/1.6m
Weight	123lbs / 56kg
Circuit Breaker Required	15A/120V
Connector (plug)	NEMA 5-15P
Sound Rating	80 Db
Included Filter Bags	70 Micron, 40 Micron
Certifications	CSA

### T4 TRIM SAVER ACCESSORIES & COMPONENTS

40 Micron Bag	23-0101-00
70 Micron Bag	23-0162-00
6" Hose - 6' Long	23-0199-00
6" Hose Cuff	23-0132-00
5" Vacuum Hose Cuff	23-01-002127
5" Vacuum Hose	23-01-127675
Vacuum Bypass T4	23-0258-P
Gasket (8" separator for cyclone)	23-0241-00
Gasket (stainless bin lid)	23-0244-00
Gasket (cyclone outlet)	23-0234-00
Stainless Steel Bin & Upgrade Kit	23-0245-00
Cyclone Cleaning Upgrade Kit	23-0265-00

Visit [twistertrimmer.com](http://twistertrimmer.com) or call your Twister Rep for an extensive list of replacement parts or accessories.

